



RFID

Password

Metal

Access Control

Matellic case and touch keypad
Combined ID&IC card together
Slim design: 140*42*18mm, for door
with slim frame

Touch Key Anti-duplicate Anti-passback



	Working Mode	Online/Offline
Basic	Working Mode	
	Algorithm	THbio_3.0
	Verification Method	ID card \ IC Mifare \ PIN
	Card Capacity	5,000
	PIN Capacity	5,000
	Record	100,000
	Verification Speed	≤1.0S
	Verification Mode	1: N, 1: 1
	FRR	<0.01%
	FAR	<0.0001%
	Display	2.0-inch TFT color screen
	Input	Touch keyboard, T9 input
	Language	English, Arabic and So on
	Voice	English, Arabic and So on
Communication	Communication	TCP/IP (LAN), USB disk,WG26/34, RS-485, RS-232
	Time Zone	8 day time zone, 8 week time zone, 5 lock combination, and support multiple people verification
	Anti-Tamper	YES
	Door Bell	YES
	Door Sensor	YES
Professional	Exit Button	YES
Access	Lock Signal	1 set relay output
Control Function	Wiegand Signal	Wiegand In/Out
	Alarm Signal	2 set signal (anti-tamper/threaten/ door open/force)
	Anti pass back	Indoor/Outdoor
	Interlock	A/B doors
	Fire Alarm	YES
	Dimension	140*42*18mm









