

SWING SPEED AUTOMATIC ENTRANCE GATE

MODEL: ST- SWA01

SMART TECHO

Swing Speed Automatic Entrance Gate,
EASY TO INSTALL, SAFE TO USE AND SIMPLE TO MANAGE.



INTRODACTION

SMART TECHO Swing Speed Automatic Entrance Gate for Internal Installation Motorized sliding two-parting wings

Architects and Interior Designers have always been at the forefront in introducing new materials.

SMART TECHO embraces this philosophy in the Speed Stile ST- SWA01 series with exciting new materials, selection of finishes and lighting effects. Finishes and ergonomic shapes that capture the designer's imagination. A new stylish and flexible design able to virtually blend infinite aesthetics within architectural interior needs, still including security features and performances from smart techno experience.

Applications:

Supermarkets

Automatic swing gate for supermarket 1200X1080mm

1. It is used to indicate the right direction of entry for customers and prevent them to enter from wrong direction.
2. Material: The primary gate shaft is made with 115CM*4.5mm flawless steel pipe; The standing pole is made with 100CM*3mm steel pipe; The horizontal pole is made with 25*1mm steel pipe. All of these are chrome plated.
3. The standard gate wide is 1 meter. It can be changed according to the request of customers, but it cannot be more than 1.2 meters.
4. There are spare holes on the standing pole and it can fit all the gates and guardrails series.

Specifications

Dimensions	L1200 × w 180 × h 1000 (mm)
the tube's diameter & Thickness	133mm & 3mm
Swing direction	one way
direction in an emergency	Push the swing arm to reverse direction in an emergency
Movement method	Sensors
Rotation of the retract lever	90 degree
Case material	304 stainless steel
Baffle material	Stainless steel
Power supply voltage	DC 24 ± 10% v, 50 Hz
access speed	30-40 / min
Indicator light	Traffic direction indication
Speed	30 people / min (semi-automatic)
Working environment	waterproof and dustproof grade above IP32
Temperature	- 10 °C - 50 °C
Humidity	≤ 90%, no condensation
Certification	ROHS , CE

Dimensions (mm)

