

X-Ray Baggage Scanner Model: STXR-6040C

SMART TECHO X-RAY Baggage Scanner

With us, your life is safe and stable

Safe to use & Simple to manage



Introduction:-

STXR-6040C Single Energy X-ray Inspection System:

STXR-6040C uses reliable high quality X-ray generator. With the superb image algorithm, STXR-6040C could offer clear scanning image, which allows operators to identify potential threat items visually. STXR-6040C X-ray inspection system increases the operator's ability to identify potential threats; the device is designed to scan briefcases, carry-on baggage, small cargo parcels. With ergonomic modern design, STXR-6040C could help operators to identify suspicious items fast and accurately.* Kindly note: STXR-6040C equipped with a computer keyboard

Application field:-

Entertainment venues, tourist attractions, office buildings, shopping malls, factories, etc.;
Suitable for security inspection of briefcase, hand luggage, postal parcels and other small package



High Light:-

1. Black white and Pseudo color display
2. Windows 10 operation system
3. With independent industrial computer
4. Professional multi-function operation

Keyboard functions:

1. Automatic save scanned image;
2. Reliable performance;
3. Friendly Image processing interface



Technical characteristics:-

1. multi-energy penetration system;
2. New radiation protection technology
3. TIP program;
4. Clear and distinct image;
5. Scanned imaged can zoom up to 64 times
6. Integrated structure design, refinement appearance
7. the latest ASIC all-digital solution design,
8. RTOS real-time image processing system

Specifications

General Specifications

Model	STXR-6040C
Channel size	605 * 405 mm (width * height)
Conveyor speed	0.22m / s (adjustable)
Conveyor Max Load	160 kg
Steel penetration	38 mm
Line resolution	> 38 AWG
Spatial resolution	Horizontal/vertical Φ 1.0mm

X-ray Generator

Tube voltage	140~160kV (multi-energy)
Direction	upward or downward
Tube current	0.6 ~ 1.2 mA (adjustable)
cooling	Sealed oil cooling / 100%
Duty cycle	100%, no preheating
Beam divergence angle	Diagonally 80 °
Protection function	Over voltage, over current, over temperature protection

Radiation Safety Indicators

X-ray Leakage	<0.5 Gy/h (at a distance of 5cm From external housing)
Single dose:	<5.0μGy
Film Safety	Safety on the ISO1600
Lead curtain	The main body is protected by a 2 ~ 4mm lead plate to ensure that the peripheral radiation of the equipment meets the national safety standards

Image & Video

Color Image Display	6 Color Imaging / 32-bit true color display
X-ray sensor	L-Shaped Photodiode Array(multi-energy), 24bit Deep
Enlarge	Fractionated gain above 64 rate, dynamic zoom display
Edge enhancement	The outline of objects more clear edge
Super image enhancement	Clearer image details
Video Card	1 GIGA
Audible/Visible Alarm	It can set alarm value, will give sound and visible signal when conforming to condition
Image Playback:	Quickly scan and display arbitrary images saved
Image Storage	Storage real-time pictures in different forms as

BMP, JPG, PNG etc. , arbitrary image processing,
continuously store

Max. Storage

Up to 200,000 scanned images

Installation Data

Weight

500 Kg (including wooden box)

Power Requirements

AC220V±10%, 60Hz±5Hz

Power consumption

0.4 KW (MAX)

Packing size

1950mm(L)*1005mm(W)*1500mm(H), 2.93cbm

Environmental Condition:

Operating Temperature

0°C~ +45°C/

Storage Temperature

-20°C~ +60°C

Humidity

20%-95%, non-condensing

Noise level

<58 dB(A)

COMPUTER

operation system

Windows 10 operation system

Processor (QC-2.24GHz)

Intel(R) Celeron(R) CPU G1840 @2.80GHz 2.80Ghz

Display

High-resolution 21-inch LED Monitor

Memory Onboard

4 GB RAM

Hard

1TB

Video Card:

1 GB Video Card

certificates

certificates

ISO 9001 : CE/FC/ ROH

Dimensions:

